

Solaris XE Lab for Waters - N2 solution for ACQUITY™ QDa™

Application: Waters ACQUITY QDa Detector
A list of instruments that are compatible with Solaris XE can be found on our Waters application list.

Part number: 3300670



Description

PEAK Scientific's Solaris XE nitrogen generator offers a reliable, compressor-free gas solution that can comfortably meet the demands of most mass spectrometers within Waters' portfolio of instruments. Using our tried and tested membrane technology, Solaris XE can operate with varying flow rates (up to 35L/min of high purity nitrogen), purity (up to 99.5%) and outlet pressure can be adjusted down from 116psi.

Solaris XE for Waters has been designed in collaboration with Waters as a dedicated gas solution for the ACQUITY QDa Detector. Solaris XE is fitted with alignment blocks specifically designed to enable the generator to be stacked underneath the ACQUITY QDa in most modular stacking configurations*, providing a compact and discreet space-saving solution within the lab. Alternatively this unit can be wall mounted or free standing on a lab bench.

The Solaris XE has been engineered to provide nitrogen to laboratories that utilize an external source of compressed air, which meets a minimum quality grade of ISO 8573-1:2010 Class 1.4.1.

*Please ask your local sales representative for advice on supported stacking configurations.

- **Gas types** Nitrogen
- **Integrated compressor:** No
- **Application Types:**
Waters ACQUITY QDa Detector A list of instruments that are compatible with Solaris XE can be found on our Waters application list.




Key Features

- Nitrogen up to 35L/min, up to 116 psi and up to 99.5% purity
- Variable outlet flow, pressure and purity
- Compact, stackable* system maximizing the use of valuable laboratory floor or bench space
- Color indicative LED lighting for easy status awareness
- Manufactured and tested to highest spec in UK, CE/FCC certified
- Safer and more convenient than pressurized cylinders, dewars or bulk storage
- 12 month on-site comprehensive warranty
- Backed by [PEAK Protected] global on premise servicing and technical support

*

100kg/220.4lbs



Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://peak.nt-rt.ru/> || pki@nt-rt.ru

Technical Specifications

Solaris XE Lab for Waters - N2 solution for ACQUITY™ QDa™	
Gas Type	Nitrogen
Max Gas Flow:	35
Max Output Pressure:	116psi/8bar
Max Output Pressure:	116psi/8bar
Max Purity:	99.50%*
Gas Outlets Fitting:	1 x 1/4 " BSPP
Min Inlet Pressure:	80psi/5.5bar
Max Inlet Pressure:	145psi/10bar
Min Inlet Air Quality:	ISO 8753-1:2010 Class 1.4.1**
Start Up Time:	5 min
Power Consumption:	Up to 6.9 Watts
Voltage:	100 / 230 VAC
Frequency:	50 / 60 Hz
Current:	0.1 Amp
Heat output:	25
Max Operating Temp:	30°C / 86°F
Contaminants:	Phthalate & BHT Free
Accreditations:	CE, FCC, CSA
Size (HxWxD) mm	156 x 343 x 650 mm
Size (HxWxD) Inches	6.1 x 13.5 x 25.6 inches
Generator Weight	15kg / 33lbs
Max Weight Bearing Capability	100kg / 220lbs

*

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://peak.nt-rt.ru/> || pki@nt-rt.ru